

For presentation to ICMC 2015 on November 5, 2015

Proposed Changes for a Long Overdue Revision of FIPS 140-2

Francisco Corella
fcorella@pomcor.com

Karen Lewison
kplewison@pomcor.com

FIPS is Out-Of-Date

- Federal Information Processing Standards (FIPS) are typically revised every 5 years
- FIPS 140-1: January 1994
- FIPS 140-2: May 2001
- FIPS 140-3: abandoned after drafts in 2007 and 2009
- Annexes and Implementation Guidance updates have provided revisions, but of limited scope

Technology Evolution Has Rendered FIPS 140-2 Obsolete

- Mobile devices have changed the computing landscape
 - by replacing PCs for some applications
 - by replacing smart cards for other applications
 - by enabling new kinds of applications
- FIPS 140-2 has become obsolete because it is incompatible with mobile technology
 - ISO 19790 has been suggested as a replacement of FIPS 140-2 but only makes incremental changes to FIPS 140-2 and has also become obsolete

FIPS 140 Must Be Rethought

- Three things that must change
 - Allow data encryption as alternative to tamper resistance
 - Eliminate most self-tests
 - Rethink certification
- Caveat: one thing that should not change
 - There should be no side channel suppression requirements (contemplated in Section 4.11 of FIPS 140-2 as possible in future versions)

Encryption vs. Physical Security

- FIPS 140-2 relies on physical security to define security levels
 - Tamper evidence required for level 2
 - Tamper resistance and/or response for levels 3 and 4
- Mobile devices rely on encryption for key/data protection
 - iOS: File and key encryption with a hierarchy of data encryption keys
 - Android: “Full disk” encryption
 - BYOD device management: enterprise data and keys segregated in encrypted containers

Encryption in FIPS 140-2

- Encryption does play a role in FIPS 140-2, but a very limited one
 - FIPS 140-2 requires key zeroization in some scenarios, but encrypted keys are exempted from the requirement
- No concept of hardware/cloud roots of trust for the derivation of key-encryption keys
 - Key-encryption keys must be derived from a user-supplied password (IG 7.16 refers to SP 800-132)
 - And high-entropy passwords are not practical on mobile devices
- Encryption cannot be used to raise the security level

Suggested Changes re Encryption

- Allow encryption as an alternative to physical security at levels 2 and 3
- Allow encryption in addition to physical security to achieve level 4
- Allow encryption keys to be derived from a physically protected key and/or a key stored off chip (in the cloud)

Online Authentication Methods for Retrieving a Key-Encryption Key from a Key Storage Service in the Cloud

1. Password
 - Immune against offline guessing attack after device capture
2. One-time password (OTP) generated by or delivered to separate device
3. Two-factor authentication (2FA) with PIN or password plus OTP
4. 2FA with key pair stored in the clear plus PIN or password
5. 2FA with key pair stored in the clear plus OTP
6. 2FA with key pair + PIN with PIN hashed with public key in service database
 - PIN immune against offline guessing attack breach of service database
7. Key pair regenerated from protocol credential and PIN
 - PIN immune against offline guessing attack after device capture

Disclosure: Pomcor has patents pending on methods 6 and 7

Rethinking Self-Tests

- Self-tests drain the battery and add undue latency in mobile devices
- Power-on self tests do not make sense in mobile devices
 - A mobile device only loses power if the battery is removed
- Testing an algorithm against a test vector stored with the algorithm serves no purpose
 - Attacker who changes the algorithm can change the test vector

Rethinking Self-Tests (Continued)

- Continuous testing of a random bit generator (RBG) makes sense, but what must be tested is the NOISE SOURCE, not the output of the RBG (see SP 800-90B)
- Suggestions
 - Require continuous testing of noise sources of RBGs, if noise sources are used
 - Eliminate all other self-tests

Rethinking Certification

- Certification is impossible for a cryptographic module implemented by software running on a commercial mobile device under a commercial mobile OS:
 - Hardware, OS, and software must be certified together, but are supplied by different entities
 - Hardware, OS, and software change too frequently, and on different schedules

Suggested Changes re Certification

- Allow separate role-specific certification of module components (e.g. hardware, OS, software)
 - With streamlined additional certification of a combination of components obtained by a system integrator
- Allow independent revalidation of different components at different times
- Make the certification effort commensurate to the security level

Caveat: Avoid Any Requirement to Mitigate Side-Channel Attacks

- Section 4.11 of FIPS 140-2 suggests that requirements to mitigate side-channel attacks may be added to the standard in the future
- Not a good idea:
 - Side-channel attacks can be prevented effectively by protocol-level countermeasures
 - E.g. blinding can prevent timing and electromagnetic attacks
 - But efforts to prevent algorithmic-level leakage are onerous and of limited effectiveness

Conclusion

- Mobile devices have made FIPS 140-2 obsolete
- FIPS 140-2 must be rethought
 - Major changes are needed, incremental changes are not enough
 - ISO 19790 is obsolete as well
- The proposed changes could make a future version of FIPS 140 relevant to mobile devices

Thank You for Your Attention

- Contact us for additional information and discussion:

Francisco Corella:

fcorella@pomcor.com

+1.619.770.6765

Karen Lewison:

kplewison@pomcor.com

+1.669.300.4510